

Page n. 1 of 8

Schuller Eh'klar GmbH EUROPE Im Astenfeld 6 A-4490 St. Florian Tel.: +43 (7224) 68 200 Fax.: +43 (7224) 68 282 Email: office@schuller.eu

Safety Data Sheet PRISMA COLOR RAL Spray ACRYL



Safety Data Sheet dated 6/2/2017, version 2

SECTION 1: Identification of the substance/mixture and of the company/undertaking 1.1. Product identifier Mixture identification: PRISMA COLOR RAL Spray ACRYL Trade name: 1.2. Relevant identified uses of the substance or mixture and uses advised against Recommended use: Spray painting decorative household, industrial and professional 1.3. Details of the supplier of the safety data sheet Company Schuller Eh' klar GmbH, Im Astenfeld 6, A-4490, St. Florian Tel.: +43(7224) 68200; Fax: +43 (7224) 68282 Competent person responsible for the safety data sheet: Ing. Mag. (FH) Johannes Frühwirt j.fruehwirt@schuller.eu 1.4. Emergency telephone number: Poison Control Center Austria: +43 (1) 406 43 43 SECTION 2: Hazards identification 2.1. Classification of the substance or mixture EC regulation criteria 1272/2008 (CLP): ⊘ Danger, Aerosols 1, Extremely flammable aerosol. Pressurized container: may burst if heated. Warning, Eye Irrit. 2, Causes serious eye irritation. Warning, STOT SE 3, May cause drowsiness or dizziness. Adverse physicochemical, human health and environmental effects: No other hazards 2.2. Label elements Hazard pictograms: Danger Hazard statements: H222+H229 Extremely flammable aerosol. Pressurized container: may burst if heated. H319 Causes serious eye irritation. H336 May cause drowsiness or dizziness. Precautionary statements: P101 If medical advice is needed, have product container or label at hand. P102 Keep out of reach of children. P103 Read label before use. P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. P211 Do not spray on an open flame or other ignition source. P251 Do not pierce or burn, even after use. P271 Use only outdoors or in a well-ventilated area. P405 Store locked up. P410+P412 Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122°F. P501 Dispose of contents/container in accordance with applicable regulations. Special Provisions: None Contains methyl acetate n-butyl acetate Special provisions according to Annex XVII of REACH and subsequent amendments: None 2.3. Other hazards



 Schuller Eh'klar GmbH EUROPE

 Im Astenfeld 6

 A-4490 St. Florian

 Tel.:
 +43 (7224) 68 200

 Fax.:
 +43 (7224) 68 282

 Email: office@schuller.eu

Safety Data Sheet PRISMA COLOR RAL Spray ACRYL vPvB Substances: None - PBT Substances: None Other Hazards: No other hazards

SECTION 3: Composition/information on ingredients

3.1. Substances N.A.

3.2. Mixtures

Hazardous components within the meaning of the CLP regulation and related classification:

Qty	Name	Ident. Number		Classification
>= 25% - < 30%	methyl acetate	Index number: CAS: EC: REACH No.:	607-021-00-X 79-20-9 201-185-2 01-2119459211- 47-XXXX	 2.6/2 Flam. Liq. 2 H225 3.3/2 Eye Irrit. 2 H319 3.8/3 STOT SE 3 H336 EUH066
>= 15% - < 20%	propane	Index number: CAS: EC: REACH No.:	601-003-00-5 74-98-6 200-827-9 01-2119486944- 21-0046	2.2/1 Flam. Gas 1 H220
>= 15% - < 20%	n-butyl acetate	Index number: CAS: EC: REACH No.:	607-025-00-1 123-86-4 204-658-1 01-2119485493- 29-XXXX	 2.6/3 Flam. Liq. 3 H226 3.8/3 STOT SE 3 H336 EUH066
>= 7% - < 10%	butane	Index number: CAS: EC: REACH No.:	601-004-00-0 106-97-8 203-448-7 01-2119480480- 41-xxxx	2.3/3 Aerosols 3 H229 2.2/1 Flam. Gas 1 H220
>= 2.5% - < 5%	dimethyl carbonate	Index number: CAS: EC: REACH No.:	607-013-00-6 616-38-6 210-478-4 01-2119548399- 23-XXXX	2.6/2 Flam. Liq. 2 H225
>= 2.5% - < 5%	and isobutane	Index number: CAS: EC: REACH No.:	601-004-00-0 75-28-5 200-857-2 01-2119480480- 41-xxxx	2.2/1 Flam. Gas 1 H220
>= 1% - < 2.5%	methanol	Index number: CAS: EC: REACH No.:	603-001-00-X 67-56-1 200-659-6 01-2119433307- 44-XXXX	 2.6/2 Flam. Liq. 2 H225 3.1/3/Dermal Acute Tox. 3 H311 3.1/3/Inhal Acute Tox. 3 H331 3.1/3/Oral Acute Tox. 3 H301 3.8/1 STOT SE 1 H370
>= 1% - < 2.5%	2-butoxyethanol; ethylene glycol monobutyl ether	Index number: CAS: EC: REACH No.:	603-014-00-0 111-76-2 203-905-0 01-2119475108- 36-XXXX	 3.1/4/Dermal Acute Tox. 4 H312 3.1/4/Inhal Acute Tox. 4 H332 3.1/4/Oral Acute Tox. 4 H302 3.2/2 Skin Irrit. 2 H315 3.3/2 Eye Irrit. 2 H319

SECTION 4: First aid measures

4.1. Description of first aid measures

In case of skin contact:

Immediately take off all contaminated clothing.

Areas of the body that have - or are only even suspected of having - come into contact with the product must be rinsed immediately with plenty of running water and possibly with soap.

Wash thoroughly the body (shower or bath).



Schuller Eh'klar GmbH EUROPE Im Astenfeld 6 A-4490 St. Florian Tel.: +43 (7224) 68 200 Fax.: +43 (7224) 68 282 Email: office@schuller.eu

Safety Data Sheet

PRISMA COLOR RAL Spray ACRYL

Remove contaminated clothing immediately and dispose off safely.

After contact with skin, wash immediately with soap and plenty of water.

In case of eyes contact:

After contact with the eyes, rinse with water with the eyelids open for a sufficient length of time, then consult an opthalmologist immediately.

Protect uninjured eye.

In case of Ingestion:

Do not under any circumstances induce vomiting. OBTAIN A MEDICAL EXAMINATION IMMEDIATELY.

In case of Inhalation: Remove casualty to fresh air and keep warm and at rest.

4.2. Most important symptoms and effects, both acute and delayed

None

4.3. Indication of any immediate medical attention and special treatment needed

In case of accident or unwellness, seek medical advice immediately (show directions for use or safety data sheet if possible).

Treatment:

None

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media:

CO2 or Dry chemical fire extinguisher.

Extinguishing media which must not be used for safety reasons:

None in particular.

5.2. Special hazards arising from the substance or mixture

Do not inhale explosion and combustion gases.

Burning produces heavy smoke.

5.3. Advice for firefighters

Use suitable breathing apparatus .

Collect contaminated fire extinguishing water separately. This must not be discharged into drains.

Move undamaged containers from immediate hazard area if it can be done safely.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Wear personal protection equipment.

- Remove all sources of ignition.
- Remove persons to safety.
- See protective measures under point 7 and 8.
- 6.2. Environmental precautions

Do not allow to enter into soil/subsoil. Do not allow to enter into surface water or drains.

Retain contaminated washing water and dispose it.

In case of gas escape or of entry into waterways, soil or drains, inform the responsible authorities.

Suitable material for taking up: absorbing material, organic, sand

6.3. Methods and material for containment and cleaning up

Wash with plenty of water. 6.4. Reference to other sections

4. Reference to other sections See also section 8 and 13

See also section 8 and 1

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Avoid contact with skin and eyes, inhalation of vapours and mists.

Don't use empty container before they have been cleaned.

Before making transfer operations, assure that there aren't any incompatible material residuals in the containers. Contamined clothing should be changed before entering eating areas.

Do not eat or drink while working.

See also section 8 for recommended protective equipment.

7.2. Conditions for safe storage, including any incompatibilities

Store at below 20 °C. Keep away from unguarded flame and heat sources. Avoid direct exposure to sunlight. Keep away from unguarded flame, sparks, and heat sources. Avoid direct exposure to sunlight. Keep away from food, drink and feed.

- Incompatible materials:
- None in particular.
- Instructions as regards storage premises:


Cool and adequately ventilated.

- 7.3. Specific end use(s)
- None in particular

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

methyl acetate - CAS: 79-20-9



SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Properties	Value	Method:	Notes:
Appearance and colour:	Liquid aspect (under pressure), various colours.		
Odour:	Caracteristic of solvent		
Odour threshold:	Non Dispobibile		
pH:	8		
Melting point / freezing point:	Non Disponibile		
Initial boiling point and boiling range:	Non Disponibile		
Flash point:	Inf. 0 ° C		
Evaporation rate:	Non Disponibile		
Solid/gas flammability:	Extremely flammable		
Upper/lower flammability or explosive limits:	Inf. 0°C		
Vapour pressure:	a 20°C - 4,0 bar a 50°C - 8,0 bar		
Vapour density:	N.A.		
Relative density:	0,75 - 0,80 g/ml		
Solubility in water:	NO		
Solubility in oil:	SI		
Partition coefficient (n- octanol/water):	Non Disponibile		



Schuller Eh'klar GmbH EUROPE Im Astenfeld 6 A-4490 St. Florian Tel.: +43 (7224) 68 200 +43 (7224) 68 282 Fax.: Email: office@schuller.eu

Safety Data Sheet PRISMA COLOR RAL Sprav ACRYL

Auto-ignition temperature:	Non è	
	autocomburente	
Decomposition temperature:	Non Disponibile	 -
Viscosity:	10-12	
Explosive properties:	NO	
Oxidizing properties:	NO	

9.2. Other information

Properties	Value	Method:	Notes:	
Miscibility:	N.A.			
Fat Solubility:	N.A.			
Conductivity:	N.A.			
Substance Groups relevant	N.A.			
properties				

SECTION 10: Stability and reactivity

- 10.1. Reactivity
- Stable under normal conditions
- 10.2. Chemical stability
 - Stable under normal conditions
- 10.3. Possibility of hazardous reactions None
- 10.4. Conditions to avoid
- Stable under normal conditions.
- 10.5. Incompatible materials
- Avoid contact with combustible materials. The product could catch fire.
- 10.6. Hazardous decomposition products None.

- SECTION 11: Toxicological information 11.1. Information on toxicological effects
 - Toxicological information of the product:
 - Ň.A.
 - Toxicological information of the main substances found in the product: methyl acetate - CAS: 79-20-9 LD50 (RABBIT) ORAL: 3705 MG/KG
 - methanol CAS: 67-56-1 LD50 (RAT) ORAL SINGLE DOSE: 5628 MG/KG
 - LD50 (RABBIT) SKINSINGLE DOSE: 15800 MG/KG
 - 2-butoxyethanol; ethylene glycol monobutyl ether CAS: 111-76-2 LD50 (RABBIT) ORĂĽ. 320 MG/KG

If not differently specified, the information required in Regulation (EU)2015/830 listed below must be considered as N.A.:

- a) acute toxicity;
- b) skin corrosion/irritation;
- c) serious eye damage/irritation;
 d) respiratory or skin sensitisation;
- e) germ cell mutagenicity;
- f) carcinogenicity;
- g) reproductive toxicity;
- h) STOT-single exposure;
- i) STOT-repeated exposure;
- j) aspiration hazard.
- SECTION 12: Ecological information

12.1. Toxicity

- Adopt good working practices, so that the product is not released into the environment.
- N.A.
- 12.2. Persistence and degradability
 - None
 - N.A.
- 12.3. Bioaccumulative potential
- N.A.
- 12.4. Mobility in soil N.A.
- 12.5. Results of PBT and vPvB assessment



Schuller Eh'klar GmbH EUROPE Im Astenfeld 6 A-4490 St. Florian Tel.: +43 (7224) 68 200 +43 (7224) 68 282 Fax.: Email: office@schuller.eu

S

Safety Data Sheet PRISMA COLOR RAL Spray ACRYL vPvB Substances: None - PBT Substances: None 12.6. Other adverse effects None

SECTION 13: Disposal considerations 13.1. Waste treatment methods

Recover, if possible. Send to authorised disposal plants or for incineration under controlled conditions. In so doing, comply with the local and national regulations currently in force.

SECTION 14: Transport information	
14.1. UN number	
Not classified as dangerous in the mea	ning of transport regulations.
ADR-UN number:	1950
IATA-Un number:	1950
IMDG-Un number:	1950
14.2. UN proper shipping name	
ADR-Shipping Name:	Aerosol
IATA-Technical name:	Aerosol
IMDG-Technical name:	Aerosol
N.A.	
14.3. Transport hazard class(es)	
ADR-Class:	2 5F
ADR-Label:	2
ADR - Hazard identification number:	-
IATA-Class:	2.1
IATA-Label:	2.1
IMDG-Class:	2
N.A.	
14.4. Packing group	
ADR-Packing Group:	-
IATA-Packing group:	-
IMDG-Packing group:	-
N.A.	
14.5. Environmental hazards	
Marine pollutant:	Marine pollutant
N.A.	
14.6. Special precautions for user	
IATA-Passenger Aircraft:	
IATA-Cargo Aircraft:	203
IMDG-Technical name:	Aerosol
IMDG-Page:	F-D, S-U
N.A.	
117 Transport in bull according to Appavil of	Marnal and the IDC Code

14.7. Transport in bulk according to Annex II of Marpol and the IBC Code N.A.

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture Dir. 98/24/EC (Risks related to chemical agents at work) Dir. 2000/39/EC (Occupational exposure limit values) Regulation (EC) n. 1907/2006 (REACH) Regulation (EC) n. 1272/2008 (CLP) Regulation (EC) n. 790/2009 (ATP 1 CLP) and (EU) n. 758/2013 Regulation (EU) 2015/830 Regulation (EU) n. 286/2011 (ATP 2 CLP) Regulation (EU) n. 618/2012 (ATP 3 CLP) Regulation (EU) n. 487/2013 (ATP 4 CLP) Regulation (EU) n. 944/2013 (ATP 5 CLP) Regulation (EU) n. 605/2014 (ATP 6 CLP) Regulation (EU) n. 2015/1221 (ATP 7 CLP) Restrictions related to the product or the substances contained according to Annex XVII Regulation (EC) 1907/2006 (REACH) and subsequent modifications: None Volatile Organic compounds - VOCs = 622.50 g/l Volatile CMR substances = 0.00 % Halogenated VOCs which are assigned the risk phrase R40 = 0.00 % Organic Carbon - C = 0.01 Where applicable, refer to the following regulatory provisions : Directive 2012/18/EU (Seveso III) Regulation (EC) nr 648/2004 (detergents). Dir. 2004/42/EC (VOC directive)



Schuller Eh'klar GmbH EUROPE Im Astenfeld 6 A-4490 St. Florian Tel.: +43 (7224) 68 200 Fax.: +43 (7224) 68 282 Email: office@schuller.eu

Safety Data Sheet PRISMA COLOR RAL Spray ACRYL

> Provisions related to directive EU 2012/18 (Seveso III): Seveso III category according to Annex 1, part 1 Product belongs to category: P3a

15.2. Chemical safety assessment No Chemical Safety Assessment has been carried out for the mixture.

SECTION 16: Other information

- Text of phrases referred to under heading 3:
 - H225 Highly flammable liquid and vapour.
 - H319 Causes serious eye irritation.
 - H336 May cause drowsiness or dizziness.
 - EUH066 Repeated exposure may cause skin dryness or cracking.
 - H220 Extremely flammable gas.
 - H226 Flammable liquid and vapour.
 - H229 Pressurized container: may burst if heated.
 - H311 Toxic in contact with skin.
 - H331 Toxic if inhaled.
 - H301 Toxic if swallowed.
 - H370 Causes damage to organs.
 - H312 Harmful in contact with skin.
 - H332 Harmful if inhaled.
 - H302 Harmful if swallowed.
 - H315 Causes skin irritation.

Hazard class and hazard category	Code	Description
Flam. Gas 1	2.2/1	Flammable gas, Category 1
Aerosols 1	2.3/1	Aerosol, Category 1
Aerosols 3	2.3/3	Aerosol, Category 3
Flam. Liq. 2	2.6/2	Flammable liquid, Category 2
Flam. Liq. 3	2.6/3	Flammable liquid, Category 3
Acute Tox. 3	3.1/3/Dermal	Acute toxicity (dermal), Category 3
Acute Tox. 3	3.1/3/Inhal	Acute toxicity (inhalation), Category 3
Acute Tox. 3	3.1/3/Oral	Acute toxicity (oral), Category 3
Acute Tox. 4	3.1/4/Dermal	Acute toxicity (dermal), Category 4
Acute Tox. 4	3.1/4/Inhal	Acute toxicity (inhalation), Category 4
Acute Tox. 4	3.1/4/Oral	Acute toxicity (oral), Category 4
Skin Irrit. 2	3.2/2	Skin irritation, Category 2
Eye Irrit. 2	3.3/2	Eye irritation, Category 2
STOT SE 1	3.8/1	Specific target organ toxicity - single exposure, Category 1
STOT SE 3	3.8/3	Specific target organ toxicity - single exposure, Category 3

Paragraphs modified from the previous revision:

SECTION 2: Hazards identification SECTION 3: Composition/information on ingredients SECTION 8: Exposure controls/personal protection SECTION 9: Physical and chemical properties SECTION 11: Toxicological information SECTION 15: Regulatory information SECTION 16: Other information

Classification and procedure used to derive the classification for mixtures according to Regulation (EC) 1272/2008 [CLP]:

Classification according to Regulation (EC) Nr. 1272/2008	Classification procedure
Aerosols 1, H222+H229	On basis of test data
Eye Irrit. 2, H319	Calculation method
STOT SE 3, H336	Calculation method

This document was prepared by a competent person who has received appropriate training.

Main bibliographic sources:

ECDIN - Environmental Chemicals Data and Information Network - Joint Research Centre, Commission of the European Communities

SAX's DANGEROUS PROPERTIES OF INDUSTRIAL MATERIALS - Eight Edition - Van Nostrand Reinold

The information contained herein is based on our state of knowledge at the above-specified date. It refers solely to the product indicated and constitutes no guarantee of particular quality.



 Schuller Eh'klar GmbH EUROPE

 Im Astenfeld 6

 A-4490 St. Florian

 Tel.:
 +43 (7224) 68 200

 Fax.:
 +43 (7224) 68 282

 Email:
 office@schuller.eu

Safety Data Sheet PRISMA COLOR RAL Spray ACRYL

It is the duty of the user to ensure that this information is appropriate and complete with respect to the specific use intended. This MSDS cancels and replaces any preceding release.

ADR:	European Agreement concerning the International Carriage of Dangerous Goods by Road.
CAS:	Chemical Abstracts Service (division of the American Chemical Society).
CLP:	Classification, Labeling, Packaging.
DNEL:	Derived No Effect Level.
EINECS:	European Inventory of Existing Commercial Chemical Substances.
GefStoffVO: GHS:	Ordinance on Hazardous Substances, Germany. Globally Harmonized System of Classification and Labeling of Chemicals.
IATA:	International Air Transport Association.
IATA-DGR:	Dangerous Goods Regulation by the "International Air Transport Association" (IATA).
ICAO:	International Civil Aviation Organization.
ICAO-TI:	Technical Instructions by the "International Civil Aviation Organization" (ICAO).
IMDG:	International Maritime Code for Dangerous Goods.
INCI:	International Nomenclature of Cosmetic Ingredients.
KSt:	Explosion coefficient.
LC50:	Lethal concentration, for 50 percent of test population.
LD50:	Lethal dose, for 50 percent of test population.
PNEC:	Predicted No Effect Concentration.
RID:	Regulation Concerning the International Transport of Dangerous Goods by Rail.
STEL:	Short Term Exposure limit.
STOT:	Specific Target Organ Toxicity.
TLV:	Threshold Limiting Value.
TWA: WGK:	Time-weighted average German Water Hazard Class.
WGR.	German water nazaru Glass.